# Day 3 Homework Exercises

Double your impact by getting started with Design of Experiments (DoE)



#### Day 3 Homework Exercise 1 Double your impact by getting started with Design of Experiments (DoE) Designing a Fractional Factorial Experiment

You have five continuous factors, **X1** through **X5**. You'd like to conduct a screening experiment to identify important effects. You have enough time and resources to run a total of 20 trials, and you don't need to run the experiment in blocks.

In JMP use the Screening Design platform from the DOE, Classical, Two Level Screening menu to explore potential screening designs. (Hint: Enter the five continuous factors, click **Continue** and then use **Choose from a list of fractional factorial designs** to see available designs.)

Questions:

- 1. Based on the information provided, what are the potential screening designs?
- 2. Select the 2<sup>5-1</sup> (16-run) design and click **Continue**. Look at the Aliasing of Effects outline. Which effects are aliased?
- 3. Add four center points to this design and click **Make Table**. How many runs are in this design?
- 4. Look at the pattern for the center points. Describe these design points.
- 5. Run the Model script, which was saved to the data table. Which effects can you estimate?



### Day 3 Homework Exercise 1 Double your impact by getting started with Design of Experiments (DoE)

DOE - Screening Design - JMP Pro				ي ت	×								
Screening Design													
<sup>⊿</sup> Responses													
Add Response - Remove Numbe	er of Responses			📴 Fractional Factorial - JMP Pro								>	×
Response Name Y optional item		Goal Lower Limit Maximize .	Upper	Fractional Factorial ▶ Fractional Factorial Design Fractional Factori		Pattern	 X1	X2	X3	X4	<b>X</b> 5	Y	
4 Factors				<ul> <li>Screening</li> <li>Model</li> <li>Evaluate Design</li> <li>DOE Dialog</li> </ul>	1	-++-+	-1	1	1	-1	1	•	-
Continuous Disserte Numerica Categorical & Bernous Add N Factors			2		!+-	-1	-1	-1	1	-1	•		
Continuous Discrete Numeric Categorical Remove Add N Factors			3		+-+-+	1	-1	1	-1	1	•		
Name Role		Values		Z	00000	0	0	0	0	0	•		
X1 Continuous X2 Continuous X3 Continuous	inuous	-	-1 1		5	+++	-1	-1	1	1	1	•	
	inuous	-1	1	Columns (7/0)	6	i+	-1	-1	1	-1	-1	•	
A Cont	inuous	-1	1	▲ Pattern @	7	++-+-	1	1	-1	1	-1	•	
AX5 Cont	inuous	-1	1	<b>⊿</b> X1 <b>*</b>	8	+++	1	1	-1	-1	1	•	
Specify Factors			<b>▲</b> X2 <b>*</b>	9	) +++	1	-1	-1	1	1	•		
				<b>▲</b> X3 <b>*</b>	10	-+++-	-1	1	1	1	-1	•	
clicking its button. Double click on a factor name or level to edit it.				▲ X4 * ▲ X5 *	11	+	-1	-1	-1	-1	1	-	
					12	+	1	-1	-1	-1	- <mark>1</mark>	•	
Continue				<b>▲</b> Y*	13	+++	1	1	1	-1	-1		
					14	-+-++	-1	1	-1	1	•1	•	
					15	++++	1	1	1	1	1		
				Rows	16	00000	0	0	0	0	0		
				All rows 20	17	-+	-1	1	-1	-1	-1		
				Selected 0	18	00000	0	0	0	0	0	•	
				Hidden 0	19	00000	0	0	0	0	0		
				Labelled 0	20	+-++-	1	-1	1	1	-1	•	
						c						3	.~



#### Day 3 Homework Exercise 1 Double your impact by getting started with Design of Experiments (DoE) Designing a Fractional Factorial Experiment

Solutions:

1. Based on the information provided, what are the potential screening designs?

The potential screening designs are an 8-run 2<sup>5-2</sup> design, a 16-run 2<sup>5-1</sup> fractional design, or a 12-run Plackett-Burman design.

2. Select the 2<sup>5-1</sup> (16-run) design and click **Continue**. Look at the Aliasing of Effects outline. Which effects are aliased?

No effects up to 2-way interactions are aliased with other effects up to 2-way interactions. So you can estimate main effects and 2-way interactions.

3. Add four center points to this design and click Make Table. How many runs are in this design?

There are 20 runs: 16 factorial points and 4 center points.

4. Look at the pattern for the center points. Describe these design points.

The center points are all run at the midpoints of the factor levels (0).

5. Run the Model script, which was saved to the data table. Which effects can you estimate?

You can estimate all main effects and 2-way interactions. (Note that you haven't conducted this experiment, so you don't have values for the response and can't run the analysis.)



#### Day 3 Homework Exercise 2 Double your impact by getting started with Design of Experiments (DoE) Analyzing a 20-Run Custom Design

The results of many designed experiments can be found in JMP in the Sample Data Library, under the Help menu. There are several topic-specific folders in the Sample Data Library. For this practice, we use the file **Reactor 20 Custom.jmp**, which is in the Design Experiment folder.

This experiment is discussed in Box, Hunter, and Hunter (2005), and in the "Design of Experiments" chapter in the JMP Start Statistics book.

In this experiment, a chemical reactor has five 2-level continuous factors: Feed Rate, Catalyst, Stir Rate, Temperature, and Concentration. These factors are all believed to be important, along with many 2-way interactions.

The experimental goal is to find the combination of factor settings to optimize reactor output, measured as a percent. A 20-run optimal design was generated, and **Percent Reacted** was recorded for each experimental trial.



#### Day 3 Homework Exercise 2 Double your impact by getting started with Design of Experiments (DoE) Analyzing a 20-Run Custom Design

Questions:

- 1. Open the file, and use the Model script to fit the model. Which terms are significant? (Use a significance level of 0.05 and remove interactions first.)
- 2. Slowly reduce this model by removing non-significant terms (PValue > 0.05). Remove interactions first. How many terms are in the reduced model?
- 3. Use the Prediction Profiler to find settings of the factors that maximize Percent Reacted. What are the settings, and what is the predicted response at these settings?
- 4. Interpret the bracketed values for the predicted Percent Reacted. What do these values represent?



## Day 3 Homework Exercise 2 Double your impact by getting started with Design of Experiments (DoE)

#### Effect Summary

Source	LogWorth	PValue
Catalyst(1,2)	3.246	0.00057
Catalyst*Temperature	2.429	0.00372
Temperature(140,180)	2.292	0.00511 ^
Temperature*Concentration	2.134	0.00734
Concentration(3,6)	1.483	0.03291 ^
Feed Rate*Concentration	0.362	0.43489
Stir Rate*Concentration	0.316	0.48301
Feed Rate*Temperature	0.286	0.51729
Catalyst*Concentration	0.286	0.51729
Catalyst*Stir Rate	0.286	0.51729
Feed Rate(10,15)	0.147	0.71365 ^
Stir Rate*Temperature	0.121	0.75725
Feed Rate*Catalyst	0.037	0.91746
Stir Rate(100,120)	0.026	0.94097 ^
Feed Rate*Stir Rate	0.016	0.96455

Effect Summary							
Source	LogWorth		PValue				
Catalyst(1,2)	9.176		0.00000				
Catalyst*Temperature	6.423		0.00000				
Temperature(140,180)	5.998		0.00000 ^				
Temperature*Concentration	5.615		0.00000				
Concentration(3,6)	3.341		0.00046 ^				





# Day 3 Homework Exercise 2 Double your impact by getting started with Design of Experiments (DoE) Analyzing a 20-Run Custom Design

Solutions:

Open the file, and use the Model script to fit the model. Which terms are significant? (Use a significance level of 0.05 and remove interactions first) 1.

The terms Catalyst, Catalyst\*Temperature, Temperature, Temperature\*Concentration, and Concentration are significant.

Slowly reduce this model by removing non-significant terms (PValue > 0.05). Remove interactions first. How many terms are in the reduced model? 2.

The same five terms are in the reduced model: three main effects and two 2-way interactions.

Use the Prediction Profiler to find settings of the factors that maximize Percent Reacted. What are the settings, and what is the predicted response at these settings? 3

(Hint: Click the red triangle for the **Prediction Profiler**, select **Optimization and Desirability**, and then select **Maximize Desirability**.) The settings are **Catalyst (2)**, **Temperature (180)**, and **Concentration (3)**. At these settings, the predicted **Percent Reacted** is 95.227.

Interpret the bracketed values for the predicted Percent Reacted. What do these 4. values represent?

The bracketed values (91.37 to 99.08) are a 95% confidence interval for the mean **Percent Reacted** at the optimal settings. Assuming that the process is stable and that other factors can be controlled, you can be confident that the mean **Percent Reacted** will be in this range.